





R26C

R26P

R26 Series Door Phone User Manual

About This Manual

Thank you for choosing Akuvox's R26 series door phone. This manual is intended for end users, who need to properly configure the door phone. This manual is applicable to 26.0.3.xx version, and it provides all functions' configurations of R26C/P. Please visit Akuvox forum or consult technical support for any new information or latest firmware.

Note: Please refer to universal abbreviation form in the end of manual when meet any abbreviation letter.

Content

1.	l. Product Overview			
	1.1. Product Description			
	1.2. Connector Introduction	2		
	1.3. LED Status Information			
2.	ily Use4			
	2.1. Make a Call	4		
	2.2. Receive a Call	Ĺ		
	2.3. Unlock by RFID Card (Optional)	4		

1. Product Overview

1.1. Product Description

Akuvox R26X is a SIP-compliant, hands-free one button video outdoor phone. It can be connected with users Akuvox indoor monitors for remote access controlling and monitoring. Users can operate the indoor phone to communicate with visitors via voice and video, and use RFID cards to unlock the door (R26C only). It's applicable in villas, offices and so on.




Figure 1.1 Product description

1.2. Connector Introduction

Ethernet (POE): Ethernet (POE) connector, which can provide both power and network connection.

12V/GND: External power supply terminal if POE is not available.

RS485A/B: RS485 terminal.

WG_D0/WG_D1: Wiegand terminal.

DOORA/B: Trigger signal input terminal.

RelayA/B (NO/NC/COM): Relay control terminal.

12V_OUT/GND_OUT: Power output terminal.

Note: The general door phone interface diagram is only for reference.




Figure 1.2-1 R26's interface




Figure 1.2-2 General interface

1.3. LED Status Information

LED Status		Description
Blue	Always on	Normal status
	Flashing	Calling
Red	Flashing	Network is unavailable
Green	Always on	Talking on a call
	Flashing	Receiving a call
Pink	Flashing	Upgrading

2. Daily Use

2.1. Make a Call

Press the call button to dial out the predefined number or IP address. If LED turns green, it means the call has been answered.

2.2. Receive a Call

Users can use phone or indoor monitor to call R26X and R26X will answer it automatically by default. If auto answer function is disabled, pressing call button to answer incoming call.

2.3. Unlock by RFID Card (Optional)

Place the predefined RFID card on the card reader. The door phone will announce "the door is now opened" and unlock the door.

13.56MHz RF card is supported on R26C.

Abbreviations

ACS: Auto Configuration Server DNS-SRV: Service record in the Domain Name System

Auto: Automatically **FTP:** File Transfer Protocol

AEC: Configurable Acoustic and Line Echo Cancelers **GND:** Ground

ACD: Automatic Call Distribution HTTP: Hypertext Transfer Protocol

Autop: Automatical Provisioning **HTTPS:** Hypertext Transfer Protocol Secure

AES: Advanced Encryption Standard **IP:** Internet Protocol

BLF: Busy Lamp Field **ID:** Identification

COM: Common IR: Infrared

CPE: Customer Premise Equipment LCD: Liquid Crystal Display

CWMP: CPE WAN Management Protocol **LED:** Light Emitting Diode

DTMF: Dual Tone Multi-Frequency **MAX:** Maximum

DHCP: Dynamic Host Configuration Protocol **POE:** Power Over Ethernet

DNS: Domain Name System **PCMA**: Pulse Code Modulation A-Law

DND: Do Not Disturb **PCMU**: Pulse Code Modulation μ-Law

PCAP: Packet Capture

PNP: Plug and Play

RFID: Radio Frequency Identification

RTP: Real-time Transport Protocol

RTSP: Real Time Streaming Protocol

MPEG: Moving Picture Experts Group

MWI: Message Waiting Indicator

NO: Normal Opened

NC: Normal Connected

NTP: Network Time Protocol

NAT: Network Address Translation

NVR: Network Video Recorder

ONVIF: Open Network Video Interface Forum

SIP: Session Initiation Protocol

SNMP: Simple Network Management Protocol

STUN: Session Traversal Utilities for NAT

SNMP: Simple Mail Transfer Protocol

SDMC: SIP Devices Management Center

TR069: Technical Report069

TCP: Transmission Control Protocol

TLS: Transport Layer Security

TFTP: Trivial File Transfer Protocol

UDP: User Datagram Protocol

URL: Uniform Resource Locator

VLAN: Virtual Local Area Network

WG: Wiegand

Contact us

For more information about the product, please visit us at www.akuvox.com or feel free to contact us by

Sales email: sales@akuvox.com

Technical support email: techsupport@akuvox.com

Telephone: +86-592-2133061 ext.7694/8162



