

AXIS Camera Station S2216 Appliance

All-in-one recorder with PoE switch for UHD surveillance

AXIS Camera Station S2216 Appliance is an all-in-one recording solution with integrated, manageable PoE switch designed to deliver reliable high-definition surveillance with up to 4K resolution. For quick and easy installation, AXIS S2216 is preconfigured and preloaded with AXIS Camera Station video management software, and includes licenses for 16 channels plus all necessary system software. AXIS Camera Station offers an intuitive user interface that allows users to take full advantage of Axis wide range of video surveillance cameras and other IP products. With the operating system stored on a solid-state drive (SSD) and 5-year warranty, AXIS S2216 provides a reliable surveillance solution.

- > [All-in-one solution with integrated PoE switch](#)
- > [High-definition surveillance with up to 4K resolution](#)
- > [AXIS Camera Station licenses included](#)
- > [Full compatibility with Axis products](#)



AXIS Camera Station S2216 Appliance

Licenses	Includes 16 AXIS Camera Station Core Device licenses	Playback:	Supports the same split scenarios as live view Supports only one monitor
Hardware		Recording	Qualified for recording with a total recording rate up to 384 Mbit per second
Processor	Intel® Core™ i5	General	
Memory	8 GB	Operating system	Microsoft® Windows® 10 IoT Enterprise SAC Operating system recovery: yes Operating system drive: 120 GB SSD
Storage	Surveillance Class HDD Total HDD slot: 4 Free HDD slot: 2 Out-of-the-box storage: 8 TB (2x4 TB)	Operating conditions	0 °C to 40 °C (32 °F to 104 °F) Humidity: 10–90% RH (non-condensing)
RAID	RAID levels: 0, 1, 10	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Switch	16 ports integrated, 260 W total power budget Power over Ethernet (PoE) IEEE 802.3at Class 4	Approvals	EMC CNS 13438, EAC, EN 55024, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety IEC/EN 60950-1, IEC/EN 62368-1, KC-Mark, UL 62368-1, IS 13252
Graphic card	Intel® HD Graphics	Dimensions	476 x 440 x 45 mm (18.7 x 17.3 x 1.8 in), 1U chassis
Power	Max 520 W, 260 W PoE dedicated 100 – 240 V AC, 6.5–2.5 A, 50/60 Hz	Weight	11 kg (24.3 lb)
Connectors	Front side: 1x USB 3.0 1x Audio line in 1x Audio line out Rear side Switch: 16x PoE ports 10/100 Mbps 1x SFP 10/100/1000 Mbps 1x RJ45 10/100/1000 Mbps Rear side Server: 1x RJ45 10/100/1000 Mbps 2x USB 2.0 1 Displayport™ 1 HDMI port	Included accessories	Rack rails, power cord
Video		Optional accessories	Surveillance Hard Drive 4 TB available from Axis Axis desktop terminals Axis Ethernet surge protector For more accessories, see axis.com
Video streaming	Live view: 1 x 4K stream full screen 4 split x 1080p Up to 16 cameras split view Supports two monitors, maximum one 4K monitor recommended	Warranty	Recorder: 5-year warranty, see axis.com/warranty Hard drive: 3-year limited hardware warranty

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

Environmental responsibility:
axis.com/environmental-responsibility