

LTC 9210, LTC 9212, LTC 9213, and LTC 9223 Indoor/Outdoor Mounting Equipment



- ► Maximum load: 9 kg (20 lb)
- ► Attractive Appearance
- Versatile Design
- ► Adjustable Mount Heads
- Lightweight
- ► Corrosion-Resistant Finish


This series of indoor/outdoor mounting equipment is designed for fixed camera or camera housing installations up to a rated load of 9 kg (20 lb). All models are made of lightweight aluminum, and feature welded construction, providing an extremely rigid camera mount. All mounts come fully assembled.

The LTC 9210/00 is a 200 mm (8 in) column mount, constructed of 38 mm (1.5 in) OD aluminum tubing with a welded surface mounting flange. An adjustable head is included for mounting a camera or housing. The adjustable head employs hex head screws and friction washers. The top mounting plate includes three (3) mounting holes for easy installation.

The LTC 9223/00 column mount is similar to the LTC 9210/00, but with a height of 610 mm (24 in). The LTC 9212/00 is a 300 mm (12 in) wall mount constructed of 38 mm (1.5 in) OD aluminum tubing, with a welded surface mounting flange. This unit includes an adjustable head, mounted on a 90 degree angle bend, to permit mounting of a camera or housing. The adjustable head employs hex head screws, friction washers, and three (3) mounting holes for easy installation.


The LTC 9213/01 is a pole mount adaptor bracket, which facilitates mounting of the LTC 9212/00 mount and LTC 9215 Series Feed-through mounts, to a 3- to 15-inch diameter pole. Stainless steel straps are included for ease of mounting.


Installation/Configuration Notes




LTC 9210/00 Column Mount, 200 mm (8 in) LTC 9223/00 Column Mount, 610 mm (24 in)

2 | LTC 9210, LTC 9212, LTC 9213, and LTC 9223 Indoor/Outdoor Mounting Equipment






LTC 9212/00 Wall Mount, 300 mm (12 in)



Dimensional Outline for adjustable head



LTC 9213/01 Pole Mount Adapter

Technical Specifications

LTC 9210/00, LTC 9212/00, LTC 9223/00, LTC 9213/01

Indoor/Outdoor Mounts

Maximum Load	9 kg (20 lb)	
Mounting Head	Adjustable 360° pan, 180° tilt (N/A for LTC 9213/01)	
Finish	Light gray	

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180 security.sales@us.bosch.com www.boschsecurity.us

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002 F.O. BOX 80002 5600 JB Eindhoven, The Netherlands Phone: + 31 40 2577 284 Fax: +31 40 2577 330 emea.securitysystems@bosch.com www.boschsecurity.com

LTC 9210/00 20-mm (8-inch)

Column Mount

LTC 9223/00 610-mm (24-inch)

Column Mount	
Approx.Weights	
LTC 9210/00	300 g (0.6 lb)
LTC 9223/00	544 g (1.2 lb)
LTC 9213/01 Pole Mou	nt Adapter
Mounting Hardware	Two (2), 1.5 m (5 ft) stainless steel straps,(2) banding clips,(4) hex head cap screws, and (4) lockwashers are furnished with unit.
Options	TC9311PM3T strapping tool available. Refer to Data Sheet for Accessories For Domed Housings.
Approx. Weight	850 g (1.9 lb)

Ordering Information

LTC 9210/00 Column Mount	LTC 9210/00
for 8-inch, 9 kg (20 lb) max load, light gray finish	
LTC 9212/00 Wall Mount	LTC 9212/00
for 12-inch, 9kg (20lb) max load, for LTC 938x and LTC 948x series housings, light gray finish	
LTC 9223/00 Column Mount	LTC 9223/00
for 24-inch, 9 kg (20 lb) max load, light gray finish	

LTC 9213/01 Pole Mount Adapter for LTC 9210, LTC 9212 and LTC 9215, light gray finish

LTC 9213/01

Asia-Pacific: Re Robert Bosch (SEA) Pte Ltd, Security Systems Represented by

11 Bishan Street 21 Singapore 573943 Phone: +65 6258 5511 Fax: +65 6571 2698 apr.securitysystems@bosch.com www.boschsecurity.com