

# CX-DE1200 Series Delayed Egress Magnetic Lock





CX-DE1200 Series Single and Double Door delayed egress magnetic locks are designed to provide the best performance and value in healthcare, childcare, retail, and institutional applications.

The innovative human voice and LED count down timer offers immediate comprehension of status for building occupants. These rugged locks are available in a range of models, with factory default operation, to meet NFPA, BOCA and local AHJ requirements.

The CX-DE1200 is now available with optional system accessories and mounting devices for added versatility.



#### **Features**

- Single and double door models
- Nuisance Delay period 1, 2 or 3 seconds
- Voice annunciator & progressive LED count-down timer
- Choice of sensor activation:
  - Door Motion
  - Door Exit Device with momentary N/O contact
  - Push Bar with momentary N/O contact
- Auto / manual start-up on power restore
- Vandal Resistant proximity trigger sensor
- Auto sensing power input with polarity protection
- Anti-Pass back / Auto Re-Lock
- Available accessories include: sounder, speaker, reset station & mounting devices



# **SPECIFICATIONS**

VOLTAGE: 12/24 VDC +/- 10% (Auto Sensing)

CURRENT DRAW: 600mA / 350mA DPS RATING: 30 VDC, 0.1A (max.)

ATS RATING: 30 VAC / 42.4 VDC, 5A (Max.)

LOCK STATUS RELAY RATING: 30 VDC, 2A (Max.) ALARM OUTPUT RATING: 30 VDC, 2A (Max.) BOND SENSOR RATING: **CX-DE1200:** 30 VDC, 2A (Max.)

HOLDING FORCE: Up to 1,200 lbs. (544 kg.) TEMPERATURE RANGE: 32°F - 131°F (0°C to 55°C)

**DIMENSIONS:** 

ARMATURE PLATE: 2-5/8"H x 11"W x 1"D (68mm x 280mm x 25mm) LOCK: 3"H x 11"W x 3"D (76mm x 280mm x 76mm)

MODELS	DELAY RELEASE TIME (SECONDS)		NUISANCE DELAY (SECONDS)		RESET AFTER ALARM		LOCK STATUS ON POWER-UP	
	FIXED	SELECTABLE	FIXED	SELECTABLE	FIXED	SELECTABLE	FIXED	SELECTABLE
CX-DE1200/1220-N1		15 or 30		1 or 2		Manual		Locked / Unlocked
CX-DE1200/1220-N2	15			0 or 1		Manual		Locked / Unlocked
CX-DE1200/1220-N3	30			0 or 1		Manual		Locked / Unlocked
CX-DE1200/1220-N4	15			0 or 1		Manual	Unlocked	
CX-DE1200/1220-B1	15			0 or 3	Auto / Manual			Locked / Unlocked
CX-DE1200/1220-B2	30			0 or 3	Auto / Manual			Locked / Unlocked
CX-DE1200/1220-B3	15		0		Auto / Manual			Locked / Unlocked
N# = NFPA COMPLIANCE B# = BOCA COMPLIANCE								

**Local Approval:** Installations must be approved by the Authority Having Jurisdiction (AHJ). Select the operational mode that meets your application and AHJ approval.

# **ORDERING INFORMATION**

Delayed Egress Maglocks (4 wall signs included. See page 4)

# CX-DE1200

Single Door



CX-DE1200-N1, CX-DE1200-N2, CX-DE1200-N3, CX-DE1200-N4, CX-DE1200-B1, CX-DE1200-B2, CX-DE1200-B3


# CX-DE1220

Double Door (Single & Tandem)

#### Models:

CX-DE1220-N1, CX-DE1220-N2, CX-DE1220-N3, CX-DE1220-N4,

CX-DE1220-B1, CX-DE1220-B2, CX-DE1220-B3



# **ORDERING INFORMATION**

# **Mounting Accessories**

CX-DE1214-38

3/8" Spacer Bar

**SPACER BARS** - Fills the space between the door stop and header jam of the frame to provide a wide flat surface to mount the magnetic lock.

**L BRACKETS** - Used to mount the magnetic lock to the side of the frame header when the lock cannot be mounted under a header jam of the frame.



**CX-DE1214-58** 5/8" Spacer Bar




**CX-DE1215** 1" x 1-1/2" L Bracket




**CX-DE1216** 1-1/2" x 1-1/2" L Bracket



**CX-DE1217** 2" L Bracket






# System Accessories


#### CX-DE502SO

Remote Annunciator for both audio & visual distinction

The stainless steel faceplate has a piezo and tri-color LED









# CX-DESPK

Remote Speaker Station for both audio & visual distinction

3 LED color states and 8-ohm speaker for remote messaging







# **ORDERING INFORMATION**

#### **System Accessories**


# CX-DESPK15/54i


External 15-watt Audio Speaker Station

Surface Mount

Aura<sup>™</sup> PCB feature displays 3 colors for designated states








#### CX-DESPK15/55i


External 15-watt Audio Speaker Station

Flush Mount

Aura<sup>™</sup> PCB feature displays 3 colors for designated states









# CX-DESPK15SM

External 15-watt Audio Speaker Station

Surface Mount









## CX-DESPK15FM

External 15-watt Audio Speaker Station

Flush Mount







# Included with CX-DE1220

4.5" x 13" (11 cm x 32.8 cm)

4 door signs with 15 or 30 second delay options

PUSH UNTIL ALARM SOUNDS. DOOR CAN BE OPENED IN 15 SECONDS.

PUSH UNTIL ALARM SOUNDS. DOOR CAN BE OPENED IN 30 SECONDS. KEEP PUSHING. THIS DOOR WILL OPEN IN 15 SECONDS. ALARM WILL SOUND.

KEEP PUSHING. THIS DOOR WILL OPEN IN 30 SECONDS. ALARM WILL SOUND.

#### 60-57A027

Delayed Egress Sign 12" x 12" (30.5 cm x 30.5 cm)

Raised lettering and braille written language for the visually impaired.

KEEP PUSHING. THIS DOOR WILL OPEN IN 15 SECONDS. ALARM WILL SOUND.



Opening New Doors to Innovation, Quality, and Support!

