MULTI-TENANT

WATCHMAN®
Your Virtual Security Guard

XL
model

ADVANCED TELEPHONE ENTRY with
LIVE STREAMING VIDEO

Press to CALL

Press to ENTER CODE

Visitor
Incoming Call
Answer | Reject

Call in Progress
Open | End Call

TYPE CODE & PRESS 'ENTER'
1 2 3
4 5 6
7 8 9
< 0 ENTER

Surface Mount
AA1XLSM ATT
AA1XLSM VZN
AA1XLSM INT

Pedestal Mount
AA1XLPE ATT
AA1XLPE VZN
AA1XLPE INT

CELLGATE EXCLUSIVES

- Streaming video telephone entry
- NEW! Dual SIM for cellular network failover
- NEW! Voice Mail Intelligence - VMI *Device configuration required
  System ignores call when reaches voice mail and continues call tree
- Verizon or AT&T LTE service *No VoIP fees required
- Plug-and-play internet option *No VoIP fees required
- Prop open notification if gate is left open more than 3 minutes

XL FEATURES

- Built-in HID card reader
- 1 native 26-bit Wiegand expansion port
- Up to 3,000 directory listings
- Calls up to 6 app contacts and 3 voice only numbers per directory listing
- Brilliant 11" color touchscreen
- 30,000 local codes and 64,000 non-local codes

EXCLUSIVE External Camera Options

- Up to 3 external cameras

Photos
- Pixel activated photos
- Cloud-stored still photos

Video
- Pixel activated video stored on SD card
- Recording w/6-second pre-record

NEW
Watchman WXP*
Wiegand Expansion Panel
4 Door Controller
for Watchman
*See WXP sheet for details

cellgate
powered by:
verizon✓ AT&T ᵁethernet

*See external camera sheet for more details

MULTI-TENANT

WATCHMAN®
Your Virtual Security Guard

XL model

Property Management Benefits

- Programmatic enrollment/import process
- System implementation support
- Tenant self-serve call group management
- Manage multiple locations via CellGate portal
- No software required
- Time/date restrictions for Wiegand credentials
- Control gate/door on demand or with a schedule
- Prop open notification

Tenant Benefits

- See live video of visitors
- Easy to use iOS/Android app
- Tenant managed call groups
- Peace of mind through increased security

Dealer Benefits

- Easy 6-wire installation *without external camera*
- Pre-configured system
- End-to-end support
- Cellular carrier and signal strength verification
- Enables installers to test all features
- Ships with live SIM(s)

TrueCloud IoT Web Portal

Manage All Your CellGate Devices on One Dashboard

- Hosted by Microsoft Azure
- Event logs and photos with all transactions
- Create access credentials with time/date restrictions
- Manage notifications
- Administrative login privileges w/multiple user tier levels

NEW! Tiered Monthly Service Options

- Just Voice
- Voice & Photos
- Voice, Photos & Video

BENEFIT: Allows client to choose data plan based on feature utilization and budget.

Cellgate App

- Receive video/audio calls from visitors

Property Manager Can:

- Control resident app functions
- Open or hold open from anywhere
- Close on demand (override holds)
- Take photos from internal and external cameras

App Available at
App Store and Google Play

SPECIFICATIONS

External Camera Options
  Bullet Cameras
    4mm Fixed Focal Lens
    5-64mm Varifocal Lens
    2.8-12mm Varifocal Lens
  Dome Camera
    3-10.5mm Varifocal Lens

HD Camera angles:
  Horizontal: 120°
  Vertical: 64°
  Camera MP: 3MP

Power Consumption
  Hardware: 625mA (average)
  External Cam: 350mA

1 – Wiegand Expansion Port (26 bit)

3 Relays:
  Switching voltage: 30v
  Switching current: 5A

3 Digital inputs

IP65

Operating Temperature
  -20°C - 55°C

Dimensions - Surface Mount
  Height-   375mm (14.75")
  Width-   305mm (12.75")
  Depth-   95mm (3.75")
Dimensions - Pedestal Mount
  Height-   375mm (14.75")
  Width-   305mm (12.75")
  Depth-   95mm (3.75") - Bottom
            152mm (6") - Top
  All electronics are mounted inside, no external box/wiring needed.

Cellular Technology/Networks
  LTE: AT&T and Verizon
  VoIP
  Full-time IP connection

Internet – plug and play VPN – minimal router configuration

Included in box
  Watchman XL
  Power supply – 5A
  Magnetic switch
  Installation manual & user manual

Available Accessories: Flush Mount Kit includes rough-in box, finish box with trim ring, (2) external antennas)

Mounts available:
  Surface Mount (aluminum-colored powder-coated steel enclosure w/brushed aluminum faceplate)
  Pedestal mount (black powder-coated steel enclosure w/brushed aluminum faceplate)

Antenna Options
  L-bracket
  Directional panel
  Signal booster

2 YEAR limited WARRANTY