

**3340****POWERCOM SERIES SIMPLEBUS DIGITAL CALL MODULE**

SB2

Complete with 128X64 dot graphic LCD display, keypad with 16 pushbuttons illuminated from the rear with blue LED's. Also operates as coded electronic key. It is complete with electronic name directory, which stores 400 user names. Name scrolling is carried out by using two search pushbuttons or by entering the initials of the name. Once the desired user name is displayed, simply press the call pushbutton. It is also possible to send the call by entering the user code directly. User programming is carried out in a simple way using programmer Art. 1230 or by means of the software for PC Art. 1249/A. Dimensions: 112X180X40 mm. From the RI21 it is compatible with all Simplebus 2 functions and products. Allows call addressing for up to 120000 users. It also allows customisation by means of an initial welcome message and offers dual language user interface operation. It can also be used in conjunction with Simplekey electronic keys for automatic updating of names in the directory.



## 3340

# POWERCOM SERIES SIMPLEBUS DIGITAL CALL MODULE

### MAIN FEATURES

Backlighting colour:	
Vandal Resistant rating (IK code):	
Height (mm):	180
Width (mm):	112
Depth (mm):	40
Operating temperature (°C):	-25 ÷ 55
Maximum current absorption (mA):	100

### SOFTWARE/FIRMWARE SPECIFICATIONS

Number of user codes:	1000
No. of storable users:	1000

### FUNCTIONS

Key button function:	Yes
----------------------	-----

### HARDWARE SPECIFICATIONS

Total buttons:	16
----------------	----

### GENERAL DATA

Colour:	Grey
---------	------

### COMPATIBILITY

Simplebus 2 audio/video system:	Yes
Simplebus 2 audio system:	Yes

### MOUNTING/INSTALLATION

Flush-mounted:	Yes
Wall-mounted:	Yes

### AUDIO/VIDEO FEATURES

Display size (inch):	3
Display resolution (HxV - pixel):	128x64
Audio system:	Yes
Audio/video system:	Yes
Type of display:	

### CONNECTIVITY

Type of connections/ports:	RS232, RS485, Infrared
----------------------------	------------------------

The technical specifications are subject to variations without warning.



**3340**

## POWERCOM SERIES SIMPLEBUS DIGITAL CALL MODULE

### CONNECTIVITY

Infrared port:	Yes
RS232 ports:	1
RS485 ports:	1