

**3452****STAINLESS STEEL VIP DIGITAL SENSE 316 A/V ENTRANCE PANEL**

Flush-mounted entrance panel (fitted level with the wall) and 3 mm thick stainless steel plate. IK08 certified. Complete with 128x64 dot LCD graphic display and 15 buttons integrated into the plate, with no mechanical movement. Also works as electronic key code. Two search buttons are used to scroll through the names; alternatively, the first letter of the required name can be entered. Once the desired username is displayed, simply press the call button. The call can also be made by directly entering the user code. It can also be used to customise an initial welcome message and can operate with a dual user interface language. Fitted with rfid reader for local door lock control. Complete with VIP a/v unit Art. 4682HC for audio/video/door lock management, and flush-mounted box with concealed fixing screws. Dimensions 342x182x3 mm.

AWARDSDESIGN
MILANOMerlion
Awards



3452

**STAINLESS STEEL VIP DIGITAL SENSE 316 A/V ENTRANCE
PANEL**

Flush-mounted

Yes

**3452**

STAINLESS STEEL VIP DIGITAL SENSE 316 A/V ENTRANCE PANEL

**4682HC COL.AUD/VID UNIT FOR VIP SYST., IKALL SERIES.H264**

Audio-video unit for ViP system including terminal block complete with front-adjustable mini lens colour camera, LED camera lighting. Complete with terminal block and digital audio management system with Eco-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume adjustable from the front. For fitting in modules: art. 33410, 33411 and 33412. Dimensions: 102x55x38 mm.

**3459 ROOF COMPLETE WITH LEDS FOR SENSE 316 ST. STEEL ENT. PANEL**

Rain shield for 316 series panels.

**4682C VIP IKALL COLOUR CAMERA**

Audio-video unit for ViP system including terminal block complete with front-adjustable mini lens colour camera, LED camera lighting. Complete with terminal block and digital audio management system with Eco-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume adjustable from the front. For fitting in modules: art. 33410, 33411 and 33412. Dimensions: 102x55x38 mm.

**1595 120-230VAC / 33VDC POWER SUPPLY UNIT**

Power supply unit with input of 120÷230VAC, 33VDC output with 500mA continuous and 1.2A inrush current for video door entry panel. Equipped with internal protection against overcurrent and short circuits. Dimensions: 71.7x90x62 mm (4 DIN modules).