



Summary

VMAX[®] A1 Plus[™] DVRs support HD-Analog and HD-TVI signals up to 5MP and CVBS up to 960H. The DVRs offer a seamless upgrade to HD resolution for new ROI from existing coaxial infrastructure. The VMAX[®] A1 Plus[™] can record 1080p video at real-time 30fps. Up the Coax (UTC) remote configuration is available with all compatible cameras. The 8-channel DVR is available with up to 10TB of storage.


Features

- Universal HD over Coax[®] DVR records HD-Analog and HD-TVI and all analog up to 960H signals
- Advanced H.264 Linux[®] embedded DVR
- 8-channels, real time 30fps recording up to 1080p
- Up to 5MP recording resolution at a total 80fps
- PathFinder[™] auto port forwarding
- C₃[™] CMS and event server software up to 144 channels
- Event camera group recording
- Complete system analysis with real-time system and network status monitoring
- Mobile Application for iPhone[®], iPad[®], iPod[®], Android[®] Smart Phones and Tablets and Apple TV[®]
- Mac[®] compatible remote ACS software
- OSD and PTZ control via coax (UTC)
- Signal hybrid detects any camera at any output automatically.
- Instant channel swap, no need to disconnect or reboot the DVR.
- Snapshot Notify[™]: camera notifications sent to an e-mail or CMS
- 4K (3840 x 2160) True HD, VGA and Spot video outputs
- 1TB - 10TB storage options
- HDD calculation and auto recording configuration
- Thumbnail search with hour and 5-minute previews
- 10 second jump buttons for playback and fast forward
- Event notifications via e-mail, text and C₃[™] CMS and push notifications to mobile devices
- Multiplex - live, playback, recording, backup, network, configuration
- 4 audio input, 1 audio output
- 4 sensor input, 1 relay output
- Digital spot monitoring output at D1 resolution
- Simple and free DDNS service
- Push notifications via DW[®] Mobile[™]
- Easy web-based client with multi-user access
- Help menu on major functions
- Auto and manual firmware upgrades
- 5 year limited warranty

Available Models

- DW-VA1P81T - 1TB, 4CH
- DW-VA1P82T - 2TB, 8CH
- DW-VA1P83T - 3TB, 8CH
- DW-VA1P84T - 4TB, 8CH
- DW-VA1P86T - 6TB, 8CH
- DW-VA1P88T - 8TB, 8CH
- DW-VA1P810T - 10TB, 8CH

Dimensions



Specifications

VIDEO		
Operating system	Embedded Linux [®]	
System	channel	8CH
	Signals supported	Analog signal up to 960H, HD-Analog and HD-TVI up to 5MP
Video-out	Monitor	True HD, VGA and Spot outputs
	Framerate	240fps
	Resolution	HDMI: 2560x1440, 3840x2160 (4K), 800x600, 1024x768, 1280x1024, 1920x1080 VGA: 800x600, 1024x768, 1280x1024, 1920x1080 Spot: D1
	Screen mode	1, 4, 6 & 9
Audio	Input	4 inputs
	Output	1 output
Alarm	Alarm input	4 inputs
	Alarm output	1 output
Serial	1x RS485 for keyboard and PTZ control	
User interface	Graphical user interface (GUI), IR remote control, USB mouse	
PERFORMANCE		
Recording	Compression	H.264
	Recording mode	Continuous, schedules, sensor-activated, motion detection, pre and post alarm, emergency, quick backup
	Pre recording	0- 5sec
	Post recording	0-5min
	Recording rate	960x480/576 (960H): 240fps
		1280x720 (HD): 240fps
Recording resolutions	1920x1080 (HD): 240fps	
	2560x1600 (4MP): 120fps	
	2560x1944 (5MP): 80fps	
	353 x 240, 720 x 480, 960 x 480, 1280x720, 1920x1080, 2560x1600, 2560x1440, 2560x 1944	
	960x480/576 (960H): 240fps	
Playback	Playback rate	1280x720 (HD): 240fps
	1920x1080 (HD): 240fps	
	2560x1600 (4MP): 120fps	
	2560x1944 (5MP): 80fps	
	Playback resolution	1, 4, 9 & 16 Ch at 1080P (up to 4K 3840x2160)
Storage	Fast forward functions	x1, x2, x4, x8, x16, x32
	Playback functions	Intelli-search by time bar, calendar (date and time), event search and thumbnail search
	HDD interface	1x SATA HDD
Features	Max. internal storage	10TB
	HDD interface type	SATA
Features	HDD health check	Temperature, S.M.A.R.T. with e-mail notifications
	Camera color control	Via UTC
	Digital zoom	Live and playback
	Software upgrade	USB flash drive, network upgrade, FTP remote upgrade
Features	Mobile client	Mobile app for Apple [®] & Android [®] smart phones & tablets
	Covert channel	Yes
	Settings import/export	Import and export DVR settings
NETWORK		
LAN	Ethernet (1x gigabit)	
Streaming	Transmission speed live	960x480/576 (960H): 240fps
		1280x720 (HD): 240fps
		1920x1080 (HD): 240fps
		2560x1600 (4MP): 120fps
		2560x1944 (5MP): 80fps
Protocol	Fixed IP, DHCP, UPnP, DDNS	
Access	Web viewer	Live, playback and configuration up to 10 multiple connections
	Client monitoring software	Mac [®] (Apple [®] S/W), C ₃ [™] (CMS S/W)
Network features	Dual stream, separate local recording and network transmission	
	Network bandwidth control (25 Kbps - 1000 Mbps)	
	Time synchronization by NTP server ("pool.ntp.org")	
Backup device	Remote & E-mail notification, remote system reboot by IE, remote PTZ control	
	PathFinder [™] P2P service (auto port forwarding)	
System recovery after power failure	Local backup by USB and CMS over the network and FTP	
Auto-reboot and journaling file system		
GENERAL		
Operating temperature and humidity	41°F - 104°F (5°C - 40°C), less than 80% (non-condensing)	
Certification	CE & FCC & KCC & WEEE, RoHS	
Power requirements	DC12V	
Power consumption	39.6W, 3.3A	
Dimension (W x D x H)	12.4" x 9.52" x 1.77" (315 x 242 x 45 mm) (1U)	
Weight	2.86 lbs (1.3kg)	
Warranty	5 year limited	

