Crystal-Clear HD Video.





2.1MP/1080p MEGApix[®] IP camera solutions.






MEGApix[®] IP cameras deliver crystal-clear images in real-time 30fps.



MEGApix* cameras feature state-of-the-art user-friendly technology providing crystal-clear megapixel video. 2.1MP/1080p resolution at real-time 30fps provides clear images without detail loss or pixilation. Selected models include Star-Light Plus™ color in near-total darkness technology.

DW's IP cameras include Power over Ethernet (PoE), universal plug and play plus an intuitive web-based UI. MEGApix^{*} cameras remove the complexity of network-powered devices while delivering superior image quality.







CleanView[™] hydrophobic dome

coating repels water, dust

Smart DNR[™] 3D digital

True day/night with

Motion detection

Two-way audio*

noise reduction (DNR)

mechanical IR cut filter*

Auto gain control (AGC)

Backlight compensation

Auto white balance (AWB)

Programmable privacy zones









Features:

(WDR)*

2.1MP/1080p real-time 30fps

fixed lens models*

darkness technology*

True Wide Dynamic Range

• Triple or dual codecs with simultaneous streaming

(H.265, H.264, MJPEG)*

• Cold start -40°F (-40°C)*

50-140ft smart IR[™] with

intelligent camera sync*

Varifocal p-iris, auto-focus and

Star-Light Plus[™] color in near-total

Resolution Options

Star-Light Plus

and grease*

(BLC)

P-Iris, Auto Focus and **Fixed Lens Options**

- Alarm sensor input*
- Relay output*
- Web server built-in
- PoE and DC12V
- Waterproof cabling*
- ONVIF conformant, profile S
- IP66 environmental-rated dusttight and water-resistant*
- IP67 dust-tight and water-proof to 3 feet
- IP68 dust-tight and water-proof*
- IK10-rated impact-resistant*
- 5 year warranty







Star-Light Plus™ color in darkness technology

Star-Light Plus™ color in near-total darkness technology provides crisp, clear images in color in near-total darkness.





Star-Light Plus™ monochrome image in near-total darkness.




details in near-total darkness.



CleanView[™] hydrophobic dome coating

The CleanView[™] coating improves visibility by reducing water spots, dust and grease build-up on the camera dome housing's glass.





Camera view without CleanView[™] Camera view CleanView[™]



Cold Start -40°F (-40°C)

The installed heater helps the camera power up in extreme cold weather conditions where temperatures may go as low as -40°F. This makes the cameras ideal for any harsh environment installation.





True wide dynamic range (WDR)

Cameras with true WDR technology have advanced sensors that can process a wider range of lighting, allowing them to record details in complex and mixed lighting environments.





Image is under exposed

Image is over exposed



WDR image is clear and balanced



Smart IR[™]

Smart IR[™] adjusts the image for IR cameras to prevent excessive illumination.





IR light reflects from object, reducing visibility

Smart IR[™] cameras distribute the IR light evenly in the FoV



License plate recognition (LPR) camera

Capture license plates in moving vehicles at up to 50mph in extreme low light visibility.





DW IP LPR camera

Non LPR camera

Camera specifications

							H.255
MODEL # D	DWC-MV82WIAT	DWC-MV82WiA	DWC-MV82DiVT	DWC-MVA2WiAT	DWC-MVA2Wi28T	DWC-MV72Di28T	DWC-MD72Di28T
Resolution	2.1MP/1080p, 30fps						
Focal length	2.8~12mm	2.8-12mm	2.7-13.5mm	2.7~13.5mm	2.8mm		
Lens type r	Vari-focal p-iris lens with motorized-zoom and auto-focus	Motorized zoom auto-focus p-iris lens	Vari-focal lens	Vari-focal p-iris lens with motorized-zoom and auto-focus	Fixed lens		
IR LEDs	100ft range	100ft range	100ft range	100ft range 80ft range		80ft range	50ft range
Star-Light Plus™ color in near-total darkness	yes			Yes			
Housing rating	IP66-rated, IK10-rated			IP67-rated, IK10-rated IP66-rated			IK10-rated













	-					
MODEL #	DWC-MF21M28T	DWC-MF21M4TIR / DWC-MF21M4TIRDMP / DWC-MF21M8TIR	DWC-MV421D / DWC-MV421DB	DWC-MV421TIR / DWC-MV421TIRB	DWC-MV72Wi28 / DWC-MV72Wi4 / DWC-MV72Wi6	DWC-MV72Wi28A / DWC-MV72Wi4A
Resolution	ution 2.1MP/1080p, 30fps					
Focal length	2.8mm	n 4.0mm, 8.0mm 2.8-12mm 2.8mm, 4.0mm, 6.0mm		2.8mm, 4.0mm, 6.0mm	2.8mm, 4.0mm	
Lens type	Fixed lens		Motorized zoom auto-focus p-iris lens	Motorized zoom auto-focus p-iris lens	Fixed lens	Fixed lens
IR LEDs		50ft range		100ft range	50ft range	50ft range
Star-Light Plus™ color in near-total darkness						
Housing rating	IP66-ra	ted, IK10-rated	IP68-rated, IK10-rated	IP68-rated, IK10-rated	IP66-rated, IK10-rated	IP64-rated, IK10-rated

		H.265	C BH C				
MODEL #	DWC-MB421TIR	DWC-MB62DiVT	DWC-MB721M4TIR / DWC-MB721M4TIRDMP / DWC-MB721M8TIR	DWC-MC421D	DWC-MD421D / DWC-MD421DB	DWC-MD421TIR / DWC-MD421TIRB	DWC-MF2Wi4T
Resolution	2.1MP/1080p, 30fps						
Focal length	2.8-12mm	2.7-13.5mm	4.0mm, 8.0mm		2.8-12mm	2.8-12mm	4.0mm
Lens type	Motorized zoom auto-focus p-iris lens	Vari-focal lens	Fixed lens	C/CS mount lens	Motorized zoom auto-focus p-iris lens		Fixed lens
IR LEDs	120ft range	100ft range	60ft range			100ft range	50ft range
Star-Light Plus™ color in near-total darkness							yes
Housing rating	IP66-rated						IP66-rated, IK10-rated



	· · · · · · · · · · · · · · · · · · ·
MODEL #	DWC-MPTZ30X
Resolution	2.1MP/1080p, 30fps
Focal length	4.3-129mm
Lens type	Motorized zoom auto-focus p-iris lens
IR LEDs	1300ft range
Star-Light Plus™ color in near-total darkness	
Housing rating	IP66-rated



C : 866.446.3595 X : sales@dwcc.tv : www.digital-watchdog.com