

# DTK-MRJ45 Series

## RJ45 Series Modular Surge Protection



**DITEK's DTK-MRJ45** Series protects vital data lines and computerized systems from surge-induced damage. Convenient RJ connections protect four voice, data and/or signal pairs. MRJ45 Series surge protectors are easily installed at a building's incoming entry, and at the equipment being protected.

### Product Features

- Protects all four pairs, RJ45 connections
- Multi-stage, hybrid design provides the best possible protection
- Current-limiting circuitry minimizes risk to connected equipment
- Five voltage levels available to protect all types of voice/data applications
- Automatic resetting fuse and sneak current protection.

### Applications

- Central Office Lines
- Building-to-Building Runs
- Station Lines
- Low Voltage Data
- P.O.T.S. Lines

### Accessories

- DIN Rail Mounting Kit – Part Number DTK-DRK

### Technical Specifications

| DTK-MRJ45SCP                   | D  | X     | LV    | OPX   | RUV    |
|--------------------------------|--|-------|-------|-------|--------|
| <b>Service Voltage:</b>        | 5V   | 12V   | 24V   | 48V   | 130V   |
| <b>MCOV:</b>                   | 8VDC   | 18VDC | 33VDC | 66VDC | 175VDC |
| <b>Clamping Voltage:</b>       | 12V  | 22V   | 47V   | 82V   | 204V   |
| <b>Protection Modes:</b>       | Tip-Ground, Ring-Ground (All)                |       |       |       |        |
| <b>Surge Current Rating:</b>   | 2,000A/pair (5V – 48V)<br>9,000A/pair (130V) |       |       |       |        |
| <b>Max Continuous Current:</b> | 0.15 Amps                                    |       |       |       |        |

### Mechanical Characteristics

|                               |   |
|-------------------------------|---|
| <b>Connection Method:</b>     | RJ45  |
| <b>Housing:</b>               | ABS   |
| <b>Operating Temperature:</b> | -40°F - 158°F (-40°C - 70°C)                  |
| <b>Maximum Humidity:</b>      | 95% non-condensing                            |
| <b>Dimensions:</b>            | 3.0"L x 1.7"W x 1.2"H<br>(76mm x 43mm x 30mm) |
| <b>Weight:</b>                | 4 oz (113 g)                                  |

### Quality, Standards & Approval

|                          |                           |
|--------------------------|---------------------------|
| <b>Agency Approvals:</b> | UL497A                    |
| <b>Warranty:</b>         | Ten Year Limited Warranty |

Every precaution has been taken to ensure that this literature is accurate and complete. DITEK Corporation assumes no responsibility and disclaims all liability for damages resulting from the use of this information or for any errors or omissions.

