DSC

PGx901 Wireless PowerG Indoor Siren

- Visible link quality indicator on device
- 110db siren with strobe light
- Differentiated audible alerts for intrusion and fire
- Prolonged battery life (8 years with typical use)
- Dimensions: 161 x 161 x 50mm (6.44 x 6.44 x 1.75in)

Available in NA, LATAM, Europe, Africa and APAC

PGx911 Wireless PowerG Outdoor Siren

- 110db siren output
- Strobe light functionality for visual indication
- Sleek design and robust weatherproof housing (IP55)
- Fully supervised
- Prolonged battery life (8 years with typical use)
- Differentiated alarm sounds for intrusion, fire, gas and flood
- Large print screen area for customizable logos
- Dimensions: 295 x 186 x 63mm (11.63 x 7.31 x 2.5in)
- Available with Amber strobe, depending on country

Available in NA, LATAM, Europe, Africa and APAC

PGx920 Wireless PowerG Repeater

- Extends the overall wireless range
- LED indications for power failure, activity and installation performance diagnostics
- Compact and easy to install
- Front and back tamper protected
- Replacement Battery BATT1.3-4.8V
- Mains powered with 48 hour backup battery (rechargeable)
- Dimensions: 161 x 161 x 50mm (6.44 x 6.445 x 1.74in)

Available in NA, LATAM, Europe, Africa and APAC

Approval Listing and Frequency vary depending on country. Please refer to www.dsc.com for complete listings and availability.

Intrusion Detectors

Security

| WS4904P Wireless Pet-Immune PIR Detector | WS4945 Wireless Door/Window Contact | EV-DW4927SS Wireless Shock Sensor with Built-In Door/Window Contact | EV-DW4975 / EV-DW8975 Wireless Vanishing Contact | EV-DW4917 Wireless Recessed Door Transmitter | AC-100 / AC-500 Wired Glassbreak Detector | BV-500 Wired 360° Ceiling-Mount PIR Motion Detector |

| LC-100-PI Wired PIR Detector with Pet-Immunity | BV-300 Wired PIR Detector | LC-151/171 Wired Pet-Immune Dual-Tech Outdoor Motion Detectors | SS-102 Wired Shock Sensor | BV-600 Wired Dual-Element, Pet-Immune PIR Motion Detector | LC-103-PIMSK / LC-104-PIMW Wired Dual-Tech Motion Detector with Pet-Immunity | AMB-500 Addressable Ceiling-Mount PIR Detector |

| AMB-300 Addressable PIR Detector | AMB-600 Addressable Pet-Immune PIR Detector | AMP-700 / AMP-701 AMP-702 / AMP-704 Addressable Contact Modules |

Safety Sensors

Safety

| WS4936 Wireless Photoelectric Smoke Detector | WS4913 Wireless Carbon Monoxide Detector | WS4985 Wireless Flood Detector | FSA-210/410 Wired Photoelectric Smoke Detector | FSB-210 Series Addressable Photoelectric Smoke Detector |

Control Panels

| PC1864 8-64 Zone Control Panel | PC1832 8-32 Zone Control Panel | PC1616 6-16 Zone Control Panel |

Keypads, Arming Devices & Panic Buttons

Remote Control

| PK5500 64-Zone LCD Full-Message Keypad | PK5501 64-Zone LCD Picture Icon Keypad | PK5508 8-Zone LED Keypad | PK5516 16-Zone LED Keypad | PTK5507W TouchScreen Security Interface | PTK5507S TouchScreen Security Interface | WT5500-WT5500P 2-Way Wire Free Keypad (optional Proximity tag support) | WTK5504 / WTK5504P Wireless TouchScreen Arming Station |

| WS4949 2-Button Wireless Key | WS4959 5-Button Wireless Key | WT4989 2-Way Wireless Key | WS4938 1-Button Wireless Personal Panic | WS4939 4-Button Wireless Key | RFK5500 64-Zone LCD Full-Message Keypad with Built-In Wireless Receiver, 32 wireless zones | RFK5564 64-Zone Full-Message Keypad with Built-In Wireless Receiver (up to 64 wireless zones) | RFK5501 64-Zone LCD Picture Icon Keypad with Built-In Wireless Receiver, 32 wireless zones |

Repeaters, Recievers, Modules and Communicators

Communication

| WS4920 Wireless Repeater | RF5132-433 Wireless Receiver | PC5320 Multiple Wireless Receiver Module | TR5164-433 2-Way Wireless Transceiver | PC5108 8-Zone Hardwire Expander | PC5100 Addressable Zone Expander | IT-230 RS-422 Interface Module | IT-100 Serial Integration Module |

| PC5200 / PC5204 Power Supply Modules | PC5208 Programmable Output Module | 3G2060R HSPA Cellular Alarm Communicator | TL260R Internet Alarm Communicator | TL2603GR Internet & HSPA Dual-Path Alarm Communicator |