

GV-RK1352 Card Reader



The GV-RK1352 is a card reader with keypad, designed to recognize PIN codes, identification cards or both. Featured with the Wiegand and RS-485 outputs, the unit can be connected to any standard access control panel. GV-RK1352 comes with a weather sealed and IP66 compliant housing for outdoor use.

KEY FEATURES

- Card reader with keypad
- Identification card and PIN code recognition
- Weather-proof and IP66-compliant housing
- RS-485 output: 9,600 bps, connect up to 8 GV-RK1352 units
- 13.56 MHz for ISO14443A (Mifare DESFire, Mifare Plus and Mifare Classic)

SPECIFICATIONS

| CPU | 8-bit microprocessor |
|------------------------|--|
| Frequency | 13.56 MHz for ISO14443A (Mifare DESFire, Mifare Plus and Mifare Classic) |
| Wiegand Interface | Wiegand 26 / 34 bit, distance 100 m (328.1ft), 24 AWG, 13V DC min., 85 °C min |
| RS-485 | 9,600 bps, connect up to 8 GV-RK1352 / R1352 / DFR1352 units Distance 600 m (1968.50 ft), 24 AWG, 13V DC min., 85 °C min |
| Input Rating | 7.5V DC~12V DC, 200mA |
| LED | Red, Green and Blue LED |
| Beeper | Buzzer |
| Color | Black |
| Supported ID Formats | Reads GID and UID |
| Operating Temperature | -35 °C ~ 66°C / -31 °F ~ 150.8 °F |
| Operating Humidity | 10 ~ 90% RH (non-condensing) |
| Dimensions (W x H x D) | 95 x 108 x 23 mm / 3.74 x 4.25 x 0.91 in |
| Weight | 260 g / 0.57 lb |
| Ingress Protection | IP66 |
| Certification | CE, FCC, RoHS, UL, CUL |

The number of GV-RK1352 supported by GV-AS Controllers

- 1. RS485 interface only supports GeoVision controllers, while Wiegand interface supports both GeoVision and 3rd party controllers (Wiegand 26/34 Bits).
- 2. If you are using third-party cards or key fobs, the reader must be under UID mode.
- 3. Specifications are subject to change without notice.



Options

Optional devices can expand the capabilities and versatilities of your GV-Reader. Consult your sales representative for more information.

| GV-AS ID Card & GV-AS ID Key Fob | GV-AS ID Cards and GV-AS ID Key Fobs are ideal for business and residential environment, where access control is important for security reasons. The 13.56 MHz cards and key fobs are available. |
|----------------------------------|--|
| GV-MountA900 | GV-MountA900 is a mounting plate that allows you to attach GV-AS110, GV-AS1110, GV-RK1352, or GV-R1352 to a US single gang power box. |

Packing List

- 1. GV-RK1352 Card Reader
- 2. Screw x 2
- 3. Screw Anchor x 2
- 4. Front Cover Plate x 2
- 5. Software CD
- 6. Installation Guide
- 7. Warranty Card

-2-