

# CONNECTED ACCESS PORTAL, 2-DOOR CONTROLLER

Cloud-based, credentialed access control.



## KEY FEATURES

### LIFTMASTER CLOUD™

Smart Access Control Software

### CONTROLS

up to 2 Gates/Doors Each

### EASILY EXPANDABLE

Network through LiftMaster Cloud

## SMART

**MULTIPLE-ENTRANCE CONTROL** WITH LIFTMASTER CLOUD.

**ELIMINATE WIRING** BETWEEN CONTROLLERS IN MULTIPLE-ENTRANCE APPLICATIONS WITH LIFTMASTER CLOUD.

**UNIVERSAL COMPATIBILITY** WITH 26- AND 30-BIT WIEGAND-COMPATIBLE READERS, RECEIVERS AND RFID READERS.

**EXPANSIVE CAPACITY** FOR 25,000 ACTIVE CREDENTIALS STORED LOCALLY SO RESIDENTS CAN ENTER EVEN WHEN THE INTERNET IS DOWN.

**REMOTE PROGRAMMING** AND ACTIVITY MONITORING USING LIFTMASTER CLOUD.

## RELIABLE

**EASY TO INSTALL** IN NEW OR EXISTING PROPERTIES.

**BACKED-UP STORAGE** IN LIFTMASTER CLOUD ENSURES THAT DATABASES ARE NEVER LOST.

**POWER OVER ETHERNET (PoE)** ALLOWS FOR FLEXIBILITY OF DEVICE PLACEMENT.

## SECURE

**EMAIL ALERTS** LET YOU KNOW WHEN A SUSPENDED CODE IS USED OR IF AN ACTIVE CODE IS BEING OVERUSED.

**REAL-TIME ACTIVITY TRACKING** WITH LIFTMASTER CLOUD.

**CLOUD-BASED SECURITY** KEEPS DATA PROTECTED AND SAFEGUARDS RESIDENT INFORMATION.

## TOTAL SOLUTION ACCESSORIES:

### CONNECTED ACCESS PORTAL, HIGH CAPACITY

Cloud-based access control for residents and guests.



CAPXL

### CELLULAR 4G/LTE MODEM WITH WI-FI®

Makes it easy to connect CAPXL and CAP2D(s) anywhere.



CAPCELL

### PASSPORT RECEIVER

Proximity card reader compatible with all standard Wiegand protocols.



PPWR

### PASSPORT REMOTE CONTROLS

PPV3M/PPK3PHM/PPLK1-X

Visor and keychain remotes with unique credentialed IDs.



KPR2000

### WIRED KEYPAD AND PROXIMITY READER

Single-entry, multifunction controller that supports up to 2,000 users.



LMMC-MINI

### multiCLASS® SE RP10 MINI MULLION

Proximity reader for credentialed access.



LMPG2-ST

### PROXCARD II® 1326 CLAMSHELL CARD

Proximity card for credentialed access.



# MASTERFUL ENGINEERING.

CAP2D

CONNECTED ACCESS PORTAL,  
2-DOOR CONTROLLER

## CAPACITIES



- 2 Controlled Gates/Doors
- 25,000 Local Resident Capacity
- 6,000 Local Event History (FIFO) Offline from Host
- Multiple, Holiday and Hold-Open Scheduling, Including One-Time and Repeating Exceptions

## POWER



- 12V DC, Min. 1.5 Amps (Transformer Not Included)
- PoE (802.3af) Enabled Network Devices, 13 Watts Max.
- UL® Listed

## MECHANICS



- Compact Size Mounts on Standard Single Electrical-Gang Box or in a NEMA Enclosure
- LED Indicator Lights Communicate Status

4.5"



3"

1.25"



LiftMaster Cloud™



CAPCELL or  
Modem/Router

Readers



CAP2D



Have more entrances?  
Add more CAPXLs or CAP2Ds  
to meet the needs of  
any community.

LiftMaster Cloud subscription required.

## STANDARD SPECS.

ELECTRICAL

### COMMUNICATION

#### INTERNET (DYNAMIC OR STATIC IP)

- High Speed
- DSL with at Least 1 MB Download Speed
- Cellular (Optional CAPCELL)

### INPUT PORTS

- 2 Wiegand Inputs
- 2 Request-to-Exit (REX) Inputs
- 2 Supervised Inputs

### OUTPUTS

- 2 Primary Relays
- 2 Auxiliary Relays

### WARRANTY

- 2-Year

## SHIPPING.

### SHIPPING WEIGHT (in lbs.)



#### CARTON (1)

- 7 1/2" x 5" x 3"
- CAP2D
- Misc. Hardware

For Support Tools and Training Videos, Visit [LiftMasterTraining.com](http://LiftMasterTraining.com)

For More Information, Visit [LiftMaster.com/AccessControl](http://LiftMaster.com/AccessControl)

Sales Support: **800.282.6225**

Technical Support Center: **800.528.2806**

[LiftMasterDealer.CustHelp.com/App/Ask](http://LiftMasterDealer.CustHelp.com/App/Ask)

© 2017 LiftMaster All Rights Reserved  
300 Windsor Drive, Oak Brook, IL 60523  
[LiftMaster.com](http://LiftMaster.com)

UL® and the UL logo are trademarks of UL LLC © 2017 All Rights Reserved.  
Wi-Fi® is a registered trademark of Wi-Fi Alliance  
© 2017 HID Global Corporation/ASSA ABLOY AB. All rights reserved.  
LMPAENPG2DXL11/17

**LiftMaster®**