

# Vandal-proof Mifare Card Reader

## LTK1104M and LTK1104MK

### Key Features:

- PC + zinc-alloy material shell (protection level is IK 10);
- Equipped with the 32-bit high-speed processor;
- Built-in audible beeper;
- Display the reader status with LED indicator;
- DIP switch;
- RS485 and Wiegand(W26/W34) protocol;
- Watchdog design for repairing itself in case that exception occurs, to ensure the long service life of the reader;
- Dust-proof and weather-proof design;
- Read Mifare card and obtain the card No.



LTK1104M

LTK1104MK

### Properties

Power Supply	DC 12V
Working Current	≤ 500mA
Processor	32-bit
Reading Frequency	13.56MHz
Reading Range	≤ 50mm (≤ 1.97")
ID Settings	via DIP Switch
Audio Alert	Beeper
Power Consumption	≤ 2W
Keypad	No Keypad for LTK1104M; Keypad with 12 Keys (0 to 9, *, #) for LTK1104MK
Certifications	FCC, CE
LED Indicator	Power Indicator; Status LED Indicator
Working Temperature	-4° F to +149° F (-20° C to +65° C)
Working Humidity	10 % to 90 % (Non-Condensing)
Water-proof	IP65
Dimensions	4.65" × 2.99" × 0.91"(118mm × 76mm × 23mm)
Weight	≤ 1.15lb (0.52Kg)
Installing Method	Applied for 86 & 120 Gang Box