



## PS-C25T / PS-C25TU / PS-C25LT



Intelligent Dual-Relay Secured Power Supply Type C Box (PS-C25T),  
US Version (PS-C25TU), C Box without transformer (PS-C25LT)

Specifications	PS-A25T	PS-C25T	PS-C25TU	PS-C25LT
Input		230VAC 50Hz, 0.14A	16VAC, 25VA	24VAC 50Hz
Internal transformer		230/16VAC, 25VA	N/A	N/A
ACU output		12VDC, 1.2A continuous supply. (current limit)		
Lock output		5A, SPDT relay, Max Switched current: 5A, Max Switched voltage: 150VDC or 300VAC		
Auxiliary Output		5A at 30VDC or at 125VAC		
Speaker		Yes	No (8 Ohm, 0.25W minimum output)	
Battery Backup		up to 7AH Maximum charge current 1.2A		
Visual indicators		DC output LED indicator on PCB		
Additional features		Short circuit and thermal overload protection, Includes battery leads		
Communications		Rosslare proprietary protocol		
Operating Temperature		-10°C to 50°C (14°F to 122°F)		
Operating Humidity		0 to 95% (Non-Condensing)		
Dimensions H x W x D	182 x 80 x 68 mm 7.2 x 3.1 x 2.7 inch		225 x 230 x 76 mm 8.85 x 9.05 x 3 inch	
Weight	1.24kg (2.73 lbs)	2.44kg (5.38 lbs)		1.5kg (3.3 lbs)