

Long-Range Barrier Sensors

E-9626-2B190Q

2 Pairs, 26 Inches Long (66cm) **E-9643-4B190Q** 4 Pairs, 43 Inches Long (109cm) **E-9661-6B190Q** 6 Pairs, 61 Inches Long (155cm)

E-9679-8B190Q

8 Pairs, 79 Inches Long (201cm)

Features:

- Long sensor range up to 190ft (600m) outdoors, 380ft (120m) indoors
- Programmable for 4 different frequencies to reduce interference between multiple units
- Programmable response time (150/300/450/600 ms)
- Built-in heater (activates at 41°F (5°C))
- LED and buzzer alignment indicators
- For indoor or outdoor perimeter security
- End caps swivel for easy installation
- Programmable immediate trigger on simultaneous breaking of beams, or trigger after a single pair of beams is broken for at least 2 seconds
- Built-in tamper switches
- No synchronizing wires required for alignment
- Form C relay output
- Terminal block wiring
- AGC (Auto Gain Control) Circuits regulate beams to ensure operation in rain, fog, and low-temperature

Specifications:

Model Number Suffix	2B190Q	4B190Q	6B190Q	8B190Q
Number of beams	2 pairs	4 pairs	6 pairs	8 pairs
Max. range (outdoor)	190' (60m)			
Max. range (indoor)	380' (120m)			
Heater active current (Rx+Tx)	160mA@12VDC			
Current draw	20~160 mA@12VDC			
Input voltage	12~24 VDC			
Response time (receiver)	150/300/450/600 ms (DIP switch programmable)			
Alarm output	NO/NC/COM, relay output, if triggered, active for 1 sec.			
Tamper output (Tx & Rx)	1A@120VAC/1A@24VDC			
Operating temperature	-49°~131° F (-45°~55° C)			
IP Rating	IP65			
Weight (Tx & Rx) with end caps	5.5-lb (2.5kg)	7.7-lb (3.5kg)	12.1-lb (5.5kg)	14.3-lb (6.5kg)
Length	26 in (2.16 ft) (66cm)	43 in (3.58 ft) (109cm)	61 in (5.08 ft) (155cm)	79 in (6.58 ft) (201cm)
Width and depth	2 ¹ / ₄ "x1 ⁷ / ₈ " (55x49 mm)			








(6B190Q)

Sensors

(8B190Q)

Swivel Housing:

Each sensor is built with a swivel housing for flexible installations and simple alignment. To use, twist the beams up to 90°.




Sample Applications:




Skylights



Windows



Warehouses, garages, gates, and walls



Fences

CERHS NO

SECO-LARM

16842 Millikan Ave • Irvine, CA 92606 Tel: 949-261-2999 / 800-662-0800 • Fax: 949-261-7326 sales@seco-larm.com • www.seco-larm.com Copyright 2012 © SECO-LARM U.S.A, Inc. All rights reserved. The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM ENFORCER® CRIWEBUSTER® CBA SLI