

SPCE6OW 6.5", white housing, 8 Ohms

SPCE5OW 5.25", white housing, 8 Ohms

SPCE6OB 6.5", black housing, 8 Ohms

SPCE5OB 5.25", black housing, 8 Ohms

SPCE6OTW 6.5", white housing, 70V

SPCE5OTW 5.25", white housing, 70V

SPCE6OTB 6.5", black housing, 70V

SPCE5OTB 5.25", black housing, 70V



Features

Contractor Elite is far from your common speaker line. Though designed with commercial applications in mind, these speakers are built with high-performance materials and features you'd find in high-end residential installations. The Contractor Elite Outdoor speaker line provides amazing sound, stylish looks, and easy installations – all for an amazing price.

- Great sound at an affordable price
- IP66 compliant, weather resistant
- Aluminum grille for extended use in outdoor environments
- "T" models come with a selectable 70V transformer
- 5 year warranty against manufacturing defects



Speaker Specifications (6.5" Models)

RMS Output Power	60W
Max Output Power	120W
Sensitivity (1W/1M)	88dB
Maximum SPL (Pmax/1M)	102dB
Impedance	8 Ohms
Frequency Response Range	85Hz - 20kHz
Driver	6.5" polypropylene woofer, 1" silk dome tweeter
Transformer Settings (for "T" Models only)	70V (50W, 25W, 12.5W, 6W, 3W, 8 Ohms)

Speaker Specifications (5.25" Models)

RMS Output Power	40W
Max Output Power	80W
Sensitivity (1W/1M)	84dB
Maximum SPL (Pmax/1M)	100dB
Impedance	8 Ohms
Frequency Response Range	90Hz - 20kHz
Driver	5.25" polypropylene woofer, .75" silk dome tweeter
Transformer Settings (for "T" Models only)	70V (40W, 20W, 10W, 5W, 2.5W, 8 Ohms)

Operating Specifications

Dimensions	7.9" (L) x 6.6" (D) x 12.6" (H)
Speaker Grille Material	Aluminum

Operating Specifications

Dimensions	7" (L) x 5.5" (D) x 11.3" (H)
Speaker Grille Material	Aluminum



close-up image of transformer and wire terminals