

8 Channel Wireless NVR Kit with Six 2MP Wireless IP Cameras, 2TB

ZIPK8WN2

8 Channel Network Wireless Video Recorder Six 2MP Wireless IP Cameras







Key Features

EZ Wizard – for easy network and system setup

EZ Search: search events from thumbnails

EZ Record: set up recording resolutions

and recording type

EZ Copy: copy what you are playing onto a

USB flash drive

EZ App Setup: just scan a QR code with the app to view your cameras on your mobile device

Recorder Features

- Supports up to 2MP resolution for recording and playback*
- 2TB storage included
- 1 front and rear USB ports for mouse and exporting files
- HDMI output
- Motion Detection with notification alerts
- LAN port to connect to your network

What's in the box:

- NVR with 2TB hard drive
- Six 2MP Wireless cameras
- Six 45' DC power extension cables
- One 3ft Ethernet cable
- Remote control (battery included)
- HDMI cable

Camera Features (O2WK1N)

- Supports up to 2MP resolution
- 3.6mm wide angle lens
- Built in microphone
- True Day/Night operation (IR cut filter)
- PIR function with white LED deterrent
- Digital WDR
- 12VDC operation
- IR range up to 65ft (built-in IR LEDs) (depending on scene reflection)
- IP66 compliant, weather resistant



*Products are in compliance with NDAA Section 889 Part B Guidelines

Camera Specifications	
Effective Pixels	1920(H)x1080(V), 2MP
Scanning System	Progressive
Horizontal Resolution	1080p
Min. Illumination	0 lux (IR LED ON)
Focal Length	3.6mm fixed lens
Max. Aperature Ratio	F2.2
Angular Field of View	87°(H), 47°(V), 104°(D)
Operational	
Shutter Mode	Auto
Gain Control	Auto
White Balance	Auto
Wide Dynamic Range	D-WDR
Digital Noise Reduction	3DNR
PIR	Yes
Mic	Yes, built-in
Day & Night	TRUE D/N, Auto

Night Distance	40ft/12M	
Video Output	Wireless	
Wireless range	984'	
Environmental		
Operating Temperature / Humidity	-22°F ~ 122°F / Less than 90% RH Startup: 14°F ~ 122°F	
Ingress Protection	IP66	
Electrical		
Input Voltage	12VDC	
NVR Specifications		
Video		
Inputs	8CH Wireless	
Resolution	1080p	
Multi Screen Display	1/4/9/SEQ	
Live		

Max. 2MP @ 15fps (Auto fps, Auto bitrate)

65ft. (depending on scene reflection)

1080p

H.265+

1/4/9/SEQ

³Hard drives excluded. iPhone is a trademark of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 8/23/21











Frame Rate

Resolution

IR Range

Compression

Multi Screen Display



8 Channel 2MP Wireless Camera and Recorder Kit

NVR Specifications		
Operating System		
Installation Wizard	Support	
Recording		
Recording Bandwith	Up to 12Mbps	
Record Rate	Main Stream: Max. 15fps@1080p per channel	
Mode	Manual, Schedule (Continuous/Event), Event (Pre/Post)	
Event	Video Loss, Motion (Sensitivity Level 1~8), HDD (Full/Failure)	
Overwrite Modes	Off/On	
Pre-alarm	Max 8 sec for 2MP	
Post-alarm	Up to 5min (30 Sec, 1/2/5min)	
Search Mode	Date/Time, Event	
Playback Function	Stop, Pause, Play Fast Forward / backward (2x, 4x, 8x) Slow Forward (1/2x, 1/4x, 1/8x,) Step Forward / backward	
Live stream	Max. 2MP @ 15fps (Auto fps, Auto bitrate)	
Protocal Support	TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTSP, NTP, HTTP, DHCP, SMTP, DNS, DDNS	
Monitoring	Web, Mobile, Netview for PC/Mac, Speco Gray Mobile App, Apple TV and Amazon Fire TV	
Storage		
Internal HDD	1 SATA HDD Max 6TB	
Internal SD Card	Yes	
USB (Back-Up)	2 USB Ports	
File Format (Back-Up)	RF, AVI, MP4	
Interface		
Video		
HDMI	1 HDMI (1024x768, 1280x1024, 1280x720, 1440x900, 1920x1080, 2560x1440, 3840x2160) EDID (monitor resolution auto detection)	
Audio		
Simultaneous Output	VGA and HDMI	
Audio Out	No	
Connections		
Ethernet	1 RJ45 10/100 Base-T	
USB	USB 2.0, 2 ports (for mouse and backup/upgrade)	
Application Support	Mouse, Remote Control	

General	
Input Voltage/Current	12V/2A DC Adaptor
Operating Temperature/	32°F~104°F / 20% ~ 85%RH

affiliates. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 8/24/21









