

## 4100DBDL

# THE DEADBOLT SPLIT LATCH SOLUTION

THE ONLY ELECTRIC
STRIKE TO OFFER
TWO LOCKING MECHANISMS

THAT FUNCTION SEPARATELY.

ORIGINALLY DEVELOPED TO ALLOW AN OVERRIDE ON DEADBOLTS IN DORM ROOMS IN CASE OF AN EMERGENCY.

### **SOME PLACES THE 4100DBDL CAN BE USED**









NEED ONE LATCH FAIL SECURE AND THE OTHER FAIL SAFE. NO PROBLEM (SEE THE BACK FOR DETAILS)



LIST PRICE \$558


GO TO: trineonline.com/4100dbdl.php





## **4100DBDL**


# THE DEADBOLT SPLIT LATCH SOLUTION

#### **2 INDEPENDENTLY CONTROLLED**










- Independent Double Latch Strike for Mortise with Deadbolt Applications
- Supplied with 4 faceplates for a true One Box Solution
- Exceed 2,000 lbs. of Holding Force
- Exceeds 1,000,000 Life Cycles
- UL10C, Class A, 3 Hour Single Door Fire Rated
- UBC 7-2, Uniform Building Code Recognized
- · CAN4 S104, Fire Door Conformant
- Note: This unique design is handed (must be specified when ordering)

Electric Characteristics					
<u>Voltage</u>	Current/Amps	<u>Ohms</u>	Duty	Sound	
12DC	0.240	50	Intm./Cont.	Silent	
24DC	0.114	210	Intm./Cont.	Silent	
12AC @ 60h	z 0.210	50	Intm.	Buzz	
16AC @ 60h	2 0.280	50	Intm.	Buzz	
24AC @ 60h.	2 0.420	50	Intm.	Buzz	

\*\*\*Per mechanism. Note: the 4100DBDL\*\*\*
has a top and bottom mechanism.



HANDING OF DOOR IS ALWAYS DETERMINED FROM THE OUTSIDE.

### **HOW TO ORDER:**

BOTH LATCHES	4100DBDL-RH-32D
FAIL SECURE	4100DBDL-LH-32D
<b>BOTH LATCHES</b>	4100DBDL-RS-RH-32D
FAIL SAFE	4100DBDL-RS-LH-32D

TOP LATCH	4100DBDL-RST-RH-32D
IS FAIL SAFE	4100DBDL-RST-LH-32D
BOTTOM LATCH	4100DBDL-RSB-RH-32D
IS FAIL SAFE	4100DBDL-RSB-LH-32D