

NEW



SLIDE GATE OPERATOR

1600_{LBS} CAPACITY



RESIDENTIAL AND COMMERCIAL
CLASS I, CLASS II, CLASS III, AND CLASS IV VEHICULAR GATE OPERATOR

New "VFLEX" Control Board

Built-In Heater
• Cold Weather Operation
Down to -20°F

Multi-Layer Corrosion Protection
• G90 Galvanized
• Clear Zinc Plating
• UV Rated Powder Coating

Conveniently Located Manual
Release and Reset Switches

Integrated Modular Power Box
• Convenient Fuse Access
• LED Status Indicators
• Convenient Power Switch
• E-Z Access Power Outlet
• E-Z Set-up 115V/230V
• (Optional) Low Voltage
Removable Power Supply

New Redesigned Chassis
Post Mount Ready

Convenient J-Box for
High Voltage Wiring



COMPATIBLE WITH VIKING WIRELESS PRODUCTS

- Wireless Master/Slave Kit provides secure and reliable wireless communication.
- Remote access to the control board settings, programming, operator diagnostics, controls, gate status and error notifications, all from the convenience of a computer or any compatible handheld device.
- Plug & Play connection for Viking wireless expansion products.



BATTERY BACKUP

- Standard Battery Backup provides 100 continuous cycles at 100% duty cycle.
- With Viking's "True" Battery Backup System, batteries are not used during normal operation, maximizing battery life.



LIGHTNING PROTECTION

- Advanced Lightning strike protection up 20,000 volts / 10,000 Amps.
- On-board surge protection monitoring.



DIGITAL LIMITS

- Simple, push button limit setup.
- Adaptive Digital Limit control maintains open and close limit position during changing environments and power failures.



DIAGNOSTICS DISPLAY

- On-board LCD screen displays voltages, amps, gate status and diagnostics.



INTERGATED HEATER

- Built-in heater for operating temperatures down to -20°F.
- This will allow you run your operator in the coldest conditions.



SOLAR SMART

- Power Saving technology minimizes current draw while at standby.



Operational Voltage	... 24 VDC with 1/2HP Motor
Main Power Source Options	... 115 / 230 VAC Single Phase 24V AC/DC (Included Power Supply)
Battery	.. 7 AmpHr 12 VDC x 2
Max Gate Capacity	... 1600 lbs / 60'
Operating Speed	... 12" per second
Battery Backup	... 100 Full Cycles (1600 lbs)
Maximum Duty Cycle	... 100% Continuous Cycle
Operating Temperature	... - 20° F to + 158° F

WARRANTY:

**7 YEAR RESIDENTIAL
5 YEAR COMMERCIAL**



VIKING WIRELESS



SOLAR EFFICIENT OPERATION



www.vikingaccess.com • 800 908 0884