9875/9975 Mortise lock device



9875/9975 Mortise lock device for all types of single or double doors, UL listed for panic exit hardware. Devices are certified to ANSI/BHMA A156.3 2014, Grade 1. Fits stock hollow metal doors with 86 cutout and door stiles as narrow as $4\sqrt[3]{4}$ " (121mm). The 9875 device has a smooth mechanism case and the 9975 device has a grooved case. The mortise lock device is non-handed except when the following device options are used: -2 (double cylinder) or SS (signal switch).

The 7500 Mortise lock is equipped with a $^{3}/_{4}$ " (19mm) anti-friction latch bolt which is field reversible without removing the lock from the door. It has a non-handed auxiliary bolt for deadlocking and a faceplate with an adjustable bevel.

Specifications

Device functions	Device ships EO/DT/NL; Field selectable;
	For TP, K or L remove NL drive screw from device
Device lengths	3' 2'4' to 3' (711mm to 914mm) Door size
	4' 2'10" to 4' (864mm to 1219mm) Door size
Device centerline	39 ¹³ / ₁₆ " (1011mm)
from finished floor	39 ¹¹ /16" (1008mm) with mullion
Center case	8" x 2 ³ / ₄ " x2 ³ / ₈ " (203mm x 70mm x 60mm)
Mechanism case	2 ¹ / ₄ " x 2 ¹ / ₄ " (57mm x 57mm)
Projection	Pushbar neutral – 3 ¹³ / ₁₆ " (97mm)
	Pushbar depressed – 3 1/16" (78mm)
Finishes	605, 606, 612, 625, 626/626AM, 628, 710, 711 and 643e
	(619 and 630 available with 98 Series only)
Fasteners and	Includes screw pack for 1 3/4" (44mm) and
sex bolts (SNB)	$2 \frac{1}{4}$ " (57mm) thick metal or wood doors.
	(Optional 425 SNB available, see page 64 for quantities)

Accessories



7500 Mortise lock



575 Strike



Hex key dogging Comes standard on 9875/9975 mortise lock exit devices.

Features and options

Electrified options

RX Request to exit
RX2 Double request to exit

E Electric locking and unlocking trim/mortise lock

EL Electric latch retraction **QEL** Quiet electric latch retraction

SS Signal switch
CX Chexit delayed exit
ALK Alarm exit kit

WP-RX Waterproof request to exit

CON Allegion Connect

Mechanical options

-2 Double cylinderGBK Glass bead kit

PN Pneumatic latch retraction

SNB Sex bolts
SEC Security screws
WH Weep holes

Dogging feature

Hex key dogging standard

Dogging options

CD Cylinder doggingCD-CX Chexit cylinder dogging

CDSI Cylinder dogging with security indicator HDSI Hex dogging with security indicator

SD Special center case dogging
LD Less dogging

DI Dogging indicator

CI Cylinder dogging indicator

Strikes

575 – Dull black