

RANGE

Access Control

Video Intercom WiFi/LAN

WIFI-BFT-KPADII (GOOSENECK MOUNT) WIFIKPAD-II-E: (VERTICAL SURFACE MOUNT) WIFIKPAD-II-EF: (VERTICAL FLUSH MOUNT)



Surface Mount Model **BFT-WIFIKPAD-II-F**



WiFi VIDEO

- Speak to and see visitors from your smartphone or tablet.
- · Easy wireless connection to existing home wifi.
- · Long range directional patch antenna at gate (up to 30-150 yards dependent on router and environmental conditions)
- · Call up to 4 devices at the same time.
- · Get a video call from your gate / door even when you're away
- · No SIM card, no call charges (data charges may apply when phone is not connected to wifi).
- · No home phone line needed.
- · Less susceptible to lighting strikes no wire in the ground

Search WIFLPRO 2









NEW Hold open button on the App.

NEW Now includes 2 relay outputs on the App.

NEW Full duplex speech.

NEW Upgraded camera, with IR cut filter for true color by day and IR night vision.

Simple setup by mobile phone. Connect to the system video directly through your phone's or tablet's wifi, enter the pass code for the home hub wifi and your devices are connected.

View the gate/door any time with monitoring mode!

Open gates with your phone or tablet.

Built in RJ45 Ethernet socket for CAT5 cabled installs.

Can work with most open market Ethernet-Over-Mains adapters for longer range applications or professional Wi-Fi magnifiers.




BFT Americas, Inc. 6100 Broken Sound Parkway N.W. Boca Raton, FL 33487


T: +1 561 995 8155 T: US. 1877 995 8155 info.bft@bft-usa.com www.bftaccess.com www.bft-usa.com

WiFi Video Intercom

PHYSICAL MEASUREMENTS


WIFI-BFT-KPADII







WIFIKPAD-II-E (SURFACE MOUNT PANEL)



5.47

WIFIKPAD-II-EF (VERTICAL FLUSHMOUNT)

Technical Details

WIFI-BFT-KPADII (GOOSENECK MOUNT)
WIFIKPAD-II-E: (VERTICAL SURFACE MOUNT)
WIFIKPAD-II-EF: (VERTICAL FLUSH MOUNT)

WIFIKPAD-II-EF: (VERTICAL FLUSH MOUNT)		
Power Supply	24v dc (adaptor included)	
Current Consumption	80mA standby, 300mA calling	
Relay Outputs	2	
Relay Type	N/O & N/C contacts	
Relay Time	Adjustable 1-10 secs	
Relay Load	2A 24v AC max	
IP Rating	IP55	
Camera	Color, 110 degrees, 640x480 pixel	
Night Vision	Yes, by infrared illumination (now with IR cut filter)	

1.57	6		(30 D)
11.53	8.66	12.44	0
	2.8	1.69	938 238 238 238

	1
App Name	WIFI PRO 2
Audio	Full 2-way duplex and half duplex sound options
Keypad Option	Yes
Keypad Relays	3
Keypad Codes	1200
Wi-Fi Standard	802.11b/g/n
Security	6-digit passcode protected
Uplink Bandwidth	110K bits/sec
Optional Add-On: WIFI-TOUCH-II	 Wall mount touch screen monitor (1280x800 resolution), 10.1 Inch screen IPS LCD Android screen with RJ-45 interface USB port. WiFi connectable. 12VDC or POE. Complete with both wall



BFT Americas, Inc. 6100 Broken Sound Parkway N.W. Boca Raton, FL 33487 T: 1 561 995 8155
T: US. 1877 995 8155
info.bft@bft-usa.com
www.bftaccess.com
www.bft-usa.com

mount bracket and desk

stand.