

RFID/ Prox Credentials


RFID/prox credentials can be used with any 125KHz prox card reader from ZK



Key Fob



Disc



Thick / Clamshell Card



Thin / ISO Card

For customers who are already using non-ZK card readers and cards, ZK provides 125 KHz key fobs which can be clipped on to cards using a badge clip slot. If the non-ZK card does not have a badge clip slot, we also offer 125 KHz self-adhesive RFID discs.

Note

When ordering ZK readers, be sure to specify which card reader technology and cards you need PRIOR to placing your order.

Specifications

Interface

EM-4100 series prox cards with a EM / Marin S.A. memory chip.
125 KHz (generic prox 26 bit, read-only)
Passive prox/RFID responder

Dimensions

Thick Clamshell Card

Length: 3.36 in. (85.47 mm)
Width: 2.12 in. (53.85 mm)
Thickness: 0.77 in. (1.97 mm)
Badge clip slot: 0.63 in. x 0.13 in. (16 mm x 3.3 mm)

Key Fob:

1.37 in. x 0.91 in. x 0.15 in. (34.8 mm x 23 mm x 3.9 mm)

RFID Disk:

Diameter: 7/8 in. (22.22 mm)
Thickness: 1/16 in. (1.59 mm)

Thin ISO Card

Length: 3.36 in. (85.47 mm)
Width: 2.12 in. (53.85 mm)
Thickness: 0.03 in. (0.8 mm)
Badge clip slot: 0.63 in. x 0.13 in. (16 mm x 3.30 mm)

Design and Specifications subject to change without notice

ZKTeco

200 Centennial Avenue, Suite 211, Piscataway, NJ 08854, USA

+1 732-412-6007 +1 732-412-6008

sales@zktechnology.com | zktechnology.com